


25G SFP28 to 25G SFP28 AOC



1~100m

LSZH MMF

Key Features

- Support 25.78125G NRZ
- Infiniband EDR & Ethernet compatible
- Max link length of 70m on OM3 MMF or 100m on OM4 MMF
- Power consumption <1W each end
- 850nm VCSEL laser and PIN photo-detector receiver
- Operating case temperature: 0°C to +70°C
- Single 3.3V power supply
- Hot Pluggable
- RoHS Compliance

Applications

- Fiber channel
- Data center
- High Performance Computing (HPC)

Supported Standards

- SFP MSA
- SFF-8472
- IEEE 802.3by



Ordering Information

LAPP-UU1xxxC		25G SFP28 to 25G SFP28 AOC – 1~100m			
Ordering P/Ns	Description	Length	WL (nm)	Cable	NOTE
LAPP-UU1010C	200G QSFP56 to 200G QSFP56 AOC	1m	850nm	LSZH MMF	
LAPP-UU1100C	200G QSFP56 to 200G QSFP56 AOC	10m	850nm	LSZH MMF	
LAPP-UU1X10C	200G QSFP56 to 200G QSFP56 AOC	100m	850nm	LSZH MMF	

xxx define AOC cable length

Disclaimer

Images are for illustrative purposes only and may not accurately represent the actual product. Specifications and appearances are subject to change without prior notice.


The information provided in this datasheet is subject to change without notice. Lumulus Technologies assumes no responsibility for any errors or omissions. Performance may vary depending on application and operating conditions. Product specifications are provided for reference only and do not constitute a warranty.

For assistance and more information, please contact your sales representative or write to sales@lumulus.com

Lumulus Technologies, Inc. USA

Headquarter

9685 Via Excelencia Suite 106
San Diego, CA 92126
USA

 (+1) 858-397-2228

 www.lumulus.com

 sales@lumulus.com



Lumulus Technologies, Inc. (Thailand Branch)

Production Site

30/30 Moo2, Tambol Wangchula
Amphur, Wagnoi, Phranakorn
Sri Ayutthaya - 13170, Thailand

- Lumulus Tech offers 24/7 support,
- with experts ready to assist with all your technical needs and questions.



tech.support@lumulus.com



sales@lumulus.com

